

Technical Data Sheet

Version 1.0 Updated 24/06/2021

Selleys Kwik Strip

Description

Selleys Kwik Strip is a rapid action solvent-based paint and varnish remover. It is in a heavily bodied form for easy application on vertical surfaces.

Product Information

Packaging	Size
Can	250mL
Can	500mL
Can	1L
Can	4L

Uses

Suitable for removing all household paints and most industrial, marine and automotive finishes. This fast-acting paint stripper is effective on most surfaces and is best suited to working on small areas.

Features

- Fast acting
- · Washes off with water
- Thick consistency for easy non-drip application

Technical Details

Property	Typical Result	
Colour	Translucent	
Technology	Solvent Based	
Indicative data only, not intended for preparation of specifications		

Directions for Use

Use outdoors only – Methylene Chloride vapour is harmful to health on prolonged exposure. Move item to be stripped to an open, shady outdoor area to ensure adequate ventilation. Avoid inhaling fumes. Wear gloves.

- Apply a thick, even coat, 2-3mm thickness, with a paint brush. Work in small section to avoid paint rehardening.
- Allow 15 minutes for the paint to completely blister before removing with a scraper or steel wood. On delicate wood use a non-metallic scourer to remove paint to prevent damaging the wood.
- The surface can then be scrubbed, using warm water. Do not use excessive water. On fine words where there is danger of raising or swelling the grain, use methylated spirits instead.

- 4. Allow the surface to dry thoroughly before repainting.
- Wash applicator brush in water. Screw on lid tightly after use.

Tips

- Lightly sandpaper or score paint to enhance stripping.
- Work on a small section at a time to avoid paint rehardening.

Storage

Store locked up in a dry, cool, well ventilated place.

Limitations

- Not suitable for application to fibreglass, PVC, acrylics, linoleum, rubber or plastics.
- Will not remove Kalsomine, penetrating stains, and some specialist industrial finishes.
- Methylene chloride based strippers can darken some timbers.
- If clear finishing, first test stripper on an inconspicuous area
- Do not use hot air guns or torches with paint stripper.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com

Head Office 1 Gow Street, Padstow, NSW, 2211, Australia. Tel: 1300 555 205 (Aus); 0800 735 539 (NZ), Email: support.selleysau@selleys.com

All information contained in this Product Information Sheet is as accurate and up-to-date as possible at the time of printing. Products can be expected to perform as indicated in this sheet, so long as application procedures and maintenance are followed as recommended. Any other warranties that may be implied are expressly excluded, except the consumer guarantees under the Australian Consumer Law, where applicable, or any other non-excludable warranties under any State legislation, where applicable.