

No More Cracks™ Large Cracks & Holes

Description

No More Cracks™ Large Cracks & Holes ready to use filler can be used on multiple surfaces inside or outside.

Product Information

Packaging	Size
Tub	230 grams
Tub	450 grams
Tub	1kg
Tottle	230 grams

Uses

No More Cracks™ Large Cracks & Holes can be used for repairing large cracks and holes on exterior and interior surfaces. It has superior adhesion to plaster, mortar, concrete, timber and primed metal.

Features

- Interior and exterior
- Durable
- Easy to Sand
- Water Clean Up
- Minimal shrinkage

Technical Details

Property	Typical Result
Technology	Water based acrylic
Appearance	Smooth paste
Sand/Paint Time	Less than 2mm, 2-3 hours Up to 6mm, 24 hours
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Ensure the surface to be filled is clean and dry with no loose or powdery material.

Directions for Use

Use a filling blade or scraper to firmly press the filler in and scrape off excess to minimise sanding.

Allow to dry for 2-3 hours, depending on humidity.

For deeper jobs apply in 6mm layers allowing each layer to dry before applying the next layer.

Sand back with fine sand paper when dry.

Tips

For deeper holes fill in 6mm layers, allowing each layer to dry before applying in the next.

Overfill final layer only slightly to minimise sanding.

It is recommended exterior surfaces are primed before filling.

Exterior applications should be protected from rain until painted over.

For best results apply an undercoat before your top coat of paint.

Clean Up

Uncured product may be removed with water. Cured product can be removed by sanding and scraping.

Storage

Store in a cool dry place.

Limitations

- Do not use below 5°C
- Not suitable for exterior timber likely to absorb excessive amounts of water
- Where movement occurs, use Selleys No More Gaps®.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com