

No More Gaps® Interior Fast Dry

Description

Selleys No More Gaps Interior Fast Dry is the ideal solution for filling gaps and cracks around skirting boards, cornices, and inside window & door frames. The advanced skinning formulation is ideal for maintenance repairs, emergency repairs and new builds as it enables painting in just 10 minutes*, ensuring outstanding and efficient results. The water-based formulation has been designed to cope with building movement to ensure a long lasting and crack resistant finish.

Product Information

Packaging	Size	Colour
Cartridge	475 g	White

Uses

Suitable for use on:

- Plasterboard
- Wood
- Particleboard
- Cement sheeting
- Aluminium
- Glass

Features

- Fast dry. Paintable in 10 minutes.
- Flexible
- Low shrinkage

Technical Details

Property	Typical Result
Technology	Water based
Colour	White
Density	1.68
Skin Time (25°C, 50%RH)	6 minutes
Dry Peel Adhesion <Anodised Al>	30 N
Shore A Hardness <Cured product>	> 40
Elongation at Break (ASTM D412)	> 80%
Modulus at 100% Elongation (ASTM D412)	0.4 MPa
Movement Capability (ISO 9046)	Up to +/-10% (expansion joints where depth is not greater than half joint width)

Indicative data only, not intended for preparation of specifications

Paint Type	Paint Over Time (minutes)
Gloss	10
Semi Gloss	0
Low Sheen	10
Flat #	100
Ceiling #	120

Surface Preparation

Surface must be clean, dry and free from dust and grease.

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun pushing product into gap or joint.
4. Smooth with a wet gloved finger/spatula.
5. Clean up wet product with a damp cloth immediately.
6. Allow surfaces to skin prior to painting (approx. 10 minutes*).

Tips

- * To avoid paint cracking, apply to gaps (no larger than 5mm deep and 10mm wide) at temperatures above 20°C. Allow sealant to dry (as indicated in table above) before painting over. Avoid applying paint too thickly. Allow 24-48 hours before painting with oil based paints. #Longer drying times are required for flat and ceiling paints because they are highly filled (i.e. contains lower binder content than other paints). This means the paint does not flex as much when the sealant dries.

Clean Up

- Uncured product may be removed with water.
- Cured product can be removed by sanding and scraping.

Head Office 1 Gow Street, Padstow, NSW, 2211, Australia. Tel: 1300 555 205 (Aus); 0800 735 539 (NZ), Email: support.selleysau@selleys.com

All information contained in this Product Information Sheet is as accurate and up-to-date as possible at the time of printing. Products can be expected to perform as indicated in this sheet, so long as application procedures and maintenance are followed as recommended. Any other warranties that may be implied are expressly excluded, except the consumer guarantees under the Australian Consumer Law, where applicable, or any other non-excludable warranties under any State legislation, where applicable.

No More Gaps[®] Interior Fast Dry

Limitations

- For gaps between tongue and groove boards and weatherboards use No More Gaps[®] Exterior & Weatherboard.
- Where movement is excessive or for areas where contact with water is frequent, use the appropriate Selleys[®] Silicone Sealant.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com