

## No More Gaps Interior Colours

### Description

Selleys No More Gaps Interior Colours is the ideal solution for filling gaps and cracks around interiors wall joints, cabinets, and splashbacks where a colour match is desired. The water-based formulation has been designed to cope with building movement for a long-lasting and crack resistant finish.

### Product Information

Packaging	Size	Colour
Cartridge	450 g	Baked Earth
		Black
		Brilliant White
		Brown
		Cedar
		Charcoal
		Coffee
		Cream
		Hog Bristle® Half (Dulux)
		Ivory
		Light Grey
		Natural White™ (Dulux)
		Timeless Grey (Dulux)
Tranquil Retreat (Dulux)		

### Uses

Suitable for use on:

- Plasterboard
- Aluminium
- Particle Board
- Wood
- Cement sheeting
- Glass

### Features

- Excellent flexibility and crack resistance
- Low shrink
- Water clean-up
- Non-staining on building materials
- Mould and mildew resistant

### Technical Details

Property	Typical Result
Technology	Water-based
Application Temperature	5°C to 40°C

Property	Typical Result
Tooling Time	2 minutes
Skin Time	3 minutes
Tack-Free Time	18 minutes
Cure Rate	4 mm in 24 hours
	8 mm in 72 hours
Elongation	> 350%
Movement Capability (ISO 9046)	±20%

All data measured at 23°C/50% relative humidity.  
Indicative data only, not intended for preparation of specifications

### Surface Preparation

Ensure surfaces are clean, dry, and free from dust or grease.

### Directions for Use

1. Tape the area around the gap or joint with painter's tape to ensure a clean finish.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint.
4. Smooth with a wet, gloved finger or spatula immediately after application (within 2 minutes).
5. Remove tape before the product skins.

### Paintability

If required, product can be painted with both water- and oil-based paints. Wait at least 30 minutes after application before painting. Wide joints are best left for 48 hours before painting as some paints shrink during drying which can cause paint to crack.

### Clean Up

Clean up wet product using a damp cloth. Dry product should be removed using a scraper.

### Storage

For maximum shelf life, the product should be kept sealed and stored in a cool place out of direct sunlight. Store product above 5°C.

### Limitations

- Not recommended for foot-traffic areas or gaps between tongue and groove boards.
- For gaps between tongue and groove boards, and weatherboards, use No More Gaps Exterior.

# No More Gaps Interior Colours

---

## Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)