

# Sealant Remover

## Description

Selleys Sealant Remover takes the elbow grease out of removing old and unwanted sealant. It is ideal for removing sealants in a single application. It is fast-working, suitable for horizontal and vertical application, and will not harm most surfaces and finishes.

## Product Information

Packaging	Size
Tub	375 g

## Uses

Sealant Remover is suitable for areas such as baths, sinks, vanities, showers, tiles, ceramics, laminate, window frames, masonry and roofing. Suitable for use on ceramic tiles, porcelain, glass, grout, most metals, brass, laminate, most plastics, masonry, coated timber and most painted surfaces.

## Features

- Fast acting; works in 10 minutes
- Sticks vertically
- Easily applied with scraper or brush
- Suitable for various sealants such as silicone, acrylic, SMP/hybrid and polyurethane
- Leaves no residue

## Technical Details

Property	Typical Result
<b>Appearance</b>	Light beige coloured smooth paste
<b>Density</b>	0.83 @ 23°C
<b>Removal Time</b>	10 minutes
Indicative data only, not intended for preparation of specifications	

## Directions for Use

Wear protective gloves. Avoid breathing vapours. Use only in a well-ventilated area.

1. Scrape/cut off old sealant to leave only a very thin layer of less than 5 mm depth. A sealant remover tool is recommended.
2. Twist lid to open and stir product if necessary. Use a scraper or brush to spread at least a 5 mm thick layer of Sealant Remover evenly over old sealant.

3. Leave for at least 10 minutes. In some cases a second application may be required.
4. Use a scraper or sealant remover tool in a forward and backward motion to remove the softened sealant from the surface.
5. Clean any residue and tools immediately with mineral turpentine.

## Clean Up

Use mineral turpentine for best results.

## Tips

- A sealant remover tool makes initial cutting and scraping of old sealant easier
- Cutting away as much old sealant as possible will enable Sealant Remover to easier penetrate.

## Storage

Store in a cool, dry place away from sources of heat or ignition.

## Limitations

- Not suitable for rubber, EPDM and polycarbonate
- Product may affect some surfaces; test compatibility before use
- Do not leave on porous materials or acrylic-painted surfaces for extended periods
- Product will not remove staining caused by old penetrated silicone oils

## Warnings, Safety Directions and First Aid

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)