

NO MORE GAPS EXTERIOR & WEATHERBOARD

Description

Selleys No More Gaps Weatherboard is a durable, flexible acrylic gap sealant designed to cope with movement caused by temperature and weather extremes. It provides weather and UV resistance.

Product Information

Packaging	Size	Colour
Cartridge	430g	White

Uses

Ideal for small exterior sealing/filling exterior joints/gaps where movement occurs such as:

- Timber weatherboards
- Synthetic weatherboards
- Masonry walls
- Brickworks
- Tiling
- Fences
- Eaves
- Fascia boards
- Window and door frames.

Features

- Excellent adhesion on masonry, ceramic tiles, wood, plasterboard, particleboard, brick, cement sheeting, aluminium, glass.
- Superior flexibility
- UV resistant
- Mould resistant
- Maximum durability – long term resistance to cracking and crumbling.
- Water clean up
- Paintable

Technical Details

Property	Typical Result
Technology	Water-based
Colour	White
Density	1.45 ± 0.05
Application Temperature	5 to 40°C
Skin Time	30 ± 5 minutes
Tack-Free Time	45 ± 5 minutes
Tensile Strength	0.6 ± 0.05Mpa
Shore A Hardness	> 40
Elongation at Break	500% (ASTM D412)
Modulus at 100% Elongation	0.5 ± 0.1
Movement Capability	+/-25% (ISO 9046)
<small>Indicative data only, not intended for preparation of specifications</small>	

Surface Preparation

Surface must be clean, dry and free from dust, grease, flaking/powdery paint and old or crumbling caulk.

Directions for Use

- Cut seal and nozzle and fit to cartridge. Insert cartridge into caulking gun.
- Apply with caulking gun, forcing product into gap.
- Smooth out with a wet spatula, ensuring sufficient product remains in joint.
- Clean up with a damp cloth immediately.
- Allow surface to skin prior to painting (approx. 30minutes).
- Do not apply or store below 5°C
- Protect from water until firmly skinned
- Allow for longer skin and cure times in damp conditions.
- Always paint over with a quality exterior paint (water-based or solvent based).

NO MORE GAPS EXTERIOR & WEATHERBOARD

Tips

- For new weatherboard, check manufacturer's instructions before using this product.
- For maximum durability on bare exterior surfaces, apply a coat of acrylic paint and allow to dry before applying this product.
- Note that in harsh conditions, joints between boards may expand beyond product's movement capability; in such cases, re-apply product and paint over.

Clean Up

Clean up excess caulk with water using a damp cloth before it dries.

Cured caulk will need to be cut; remaining caulk can be softened with acetone and then removed.

Storage

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs.

Limitations

- Maximum gap size recommended:
Width: 12mm / Depth: 12mm.
- Not for sealing around bathtubs, kitchen sinks, etc. use No More Gaps Bathroom.
- Use the appropriate Selleys Silicone Sealant where excessive joint movement occurs or for areas prone to frequent water immersion.
- Not to be stored or applied below 5°C

Safety Directions

Wash hands after use.

Cure product before disposal

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com