

## Pro-Trade Gap Filler Smooth Finish

### Description

Pro-Trade Gap Filler Smooth Finish is a white, paintable, flexible acrylic gap sealant suitable for interior and exterior applications.

Allow to skin (about 30 minutes)\* before painting with water-based paints. If oil-based paints are to be used, or if gaps are large, allow sealant to set for about 48 hours.

### Product Information

Packaging	Size	Colour
Cartridge	475g	White

### Uses

Pro-Trade Gap Filler Smooth Finish can be used for sealing gaps and joints where anticipated movement is not in excess of +/- 10% of joint width.

### Features

- Suitable for use on wood, plasterboard, brick, glass, aluminium, ceramics, paints and many other building materials
- Flexible - will withstand joint movement of +/- 10% of joint width. Suitable for those applications where slight movement causes hard fillers to crack and fall out
- Paintable with water and oil-based paints without need of priming\*
- Weatherproof - suitable for interior and exterior applications
- Sag resistant – 0mm after 10mins Easy to apply
- Water clean up
- Low odour

### Surface Preparation

Ensure that all surfaces are dry, clean and free from dust, grease, old crumbling sealant and flaking paint.

### Directions for Use

Cut cartridge nipple, screw nozzle to cartridge and cut nozzle at an angle to desired bead size.

Apply using a caulking gun, forcing sealant into gap.

Smooth the sealant with a wet finger or knife and remove excess immediately with a damp cloth and clean tools with water.

### Technical Details

Property	Typical Result
<b>Technology</b>	Water based acrylic
<b>Colour</b>	White
<b>Density</b>	Approx. 1.58
<b>Application Temperature</b>	Above 5°C
<b>Skin Time</b> 23°C / 50% RH	20 – 30 minutes
<b>Working Time</b> 23°C / 50% RH	30 minutes
<b>Tack Free Time</b> 23°C / 50% RH	60 minutes
<b>Shore A Hardness</b> (DIN 53505)	Greater than 410
<b>Movement Capability</b> ISO 9046	+/- 10%
<b>VOC Content</b> Calculated according to the formula specified in The South Coast Air Quality Management District Rule 1168.	19g/L

Indicative data only, not intended for preparation of specifications

### Tips

\*Some water-based undercoats and flat paints may crack on drying. Test on a small section of sealant. Paint cracking may be reduced by using vinyl/acrylic semi-gloss paint or oil-based undercoat first, or by allowing full cure.

Pro-Trade Gap Filler Smooth Finish will skin in 20 - 30 minutes depending on the temperature and humidity and will achieve full cure in 7 days.

# Pro-Trade Gap Filler Smooth Finish

---

This product will take longer to cure at temperatures below 10°C, and in high humidity. Allow for longer cure times in these conditions.

## Coverage

One 475g cartridge of Pro-Trade Gap Filler Smooth Finish will produce a 6mm bead of sealant approximately 10.6m long.

## Clean Up

All tools can be cleaned up in water.

## Storage

Store in a cool dry place. Should not be stored below 0°C

## Limitations

- Pro-Trade Gap Filler Smooth Finish should not be applied below 5°C.
- Pro-Trade Gap Filler Smooth Finish should not be used outside if rain is imminent. Once applied it should be protected from rain until firmly skinned. Painting will improve exterior durability.
- Not suitable for permanent water immersion or in constantly damp areas.
- Pro-Trade Gap Filler Smooth Finish is not suitable for use in joints where joint movement is greater than +/- 10% of joint width.
- Not suitable for sealing fine joints between tongue and groove boards or weatherboard overlaps. Use No More Gaps Weatherboard for this application.

## Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)