

Permafilla

Description

Selleys Permafilla is a light grey versatile ready mixed filler, ideal for interior and exterior applications. It is suitable for timber, plaster, mortar, brick, stone, concrete and primed metal.

Product Information

Packaging	Size
Tub	280 g
Tub	630 g
Tub	1.3 kg
Tub	4.2 kg

Uses

For exterior and interior use.

Features

- Low shrinkage.
- Easy to sand.
- Excellent paintability.
- Water Clean Up
- Low Odour

Technical Details

Property	Typical Result
Technology	Water based
Appearance	Smooth grey paste
Drying time	2-3 hours in 1-2mm applications.
Shore A Hardness	60
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Surface should be clean and dry, with no loose or powder material. Exterior surfaces should be primed before application.

Directions for Use

1. Use a flexible filling knife, pressing in firmly. Remove any excess.
2. Allow to dry 2-3 hours in thin applications (1-2mm). For deeper cracks apply in 6mm layers, allowing each layer to dry before applying the next. Slightly overfill top layer for sanding.
3. Allow longer drying times in cold or humid conditions and when applying oil-based paint.
4. No need to prime before applying undercoat. Can be painted with water or oil-based paints. Clean tools with water before filler dries.
5. **EXTERIOR APPLICATIONS** must be protected from rain until dry and painted over with two coats of quality exterior paint.

Tips

Use Selleys No More Gaps where movement occurs.

For best results when painting, apply undercoat before applying water or oil based top coat.

Clean Up

Clean tools with water before filler dries. Cure product before disposal.

Storage

Store in a cool dry place.

Limitations

- Avoid using below 5°C.
- Do not nail.
- Not suitable for areas where movement occurs.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.co.nz